



Exhibit VI Mars Technology Program



Mars Technology Program Structure



Focused Technology

Base Technology

1.0	ENTRY DESCENT AND LANDING	4.0	REGIONAL MOBILITY AND SUBSURFACE ACCESS
1.1	Optical Nav	4.1	Rovers
1.2	Guided Entry	4.2	Aerial Platforms
1.3	Subsonic Parachute	4.3	Subsurface Exploration
1.4	Descent Propulsion	4.4	Science Operations & Visualization
1.5	Hazard Detection & Avoidance	5.0	SCIENCE INSTRUMENTS AND SYSTEMS
1.6	Touchdown Systems	5.1	Mars Instrument Development Porgram (NRA)
1.7	EDL Mission Simulation	5.2	In-situ Life Detection
2.0	SURFACE POWER	6.0	TELECOM & NAVIGATION
2.1	RPS Power Generation	6.1	Deep Space Communications
2.2	Solar Power Generation	6.2	Mars Proximity Communications
2.3	Power Storage	6.3	Radio Based Navigation
		6.4	Communication Protocols and Coding
3.0	SAMPLE RETURN TECHNOLOGIES	7.0	TRANSPORTATION/ORBIT INSERTION
3.1	Forward Planetary Protection	7.1	Aerocapture
3.2	Ascent Vehicle Technology	7.2	Space Propulsion
3.3	Space Rendezvous and Sample Capture	8.0	ADVANCED EDL
3.4	Sample Containment & Earth Return	8.1	Advanced EDL Technologies
3.5	Returned Sample Handling (MRSH Technology)	9.0	INFORMATION SYSTEMS
		9.1	MDS





Focused Technologies



Mars Focused Technologies EDL Technology



WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
	Design, build and test small optical navigation camera capable of providing entry corridor accuracy
	of better than 0.5km. Validate ability to use Phobos as the reference target for both precision
Optical navigation	landing and aerocapture missions.
	Develop guided entry vehicle capable of maintaining a ballistic course from entry to parachute
Guided Entry	deployment given uncertainties in atmospheric profile, winds and aerodynamic performance
	Demonstrate a low q low Mach number parachute with potential for EDL enhancements including
Subsonic Parachute	paraguidance
	Demonstrate descent engine systems including thrusters, throttle valve, and high flow presssure
	regulators for carrying out a controlled descent to the Mars surface. Recapture and improve Viking
Descent propulsion	thruster technology.
	Detect hazards such as rocks and slope that represent a hazard to the lander using an active
	sensor such as LIDAR or radar and develop a strategy for avoiding these hazards and directing the
Hazard Detection and Avoidance	lander to the nearest accessible safe site
	Demonstrate a brassboard LIDAR sensor capable of generating elevation maps of the surface of
	Mars from a lander descending towards the surface that can be used to detecting hazards such as
LIDAR	rocks and steep slopes.
	Demonstrate a robust landing system capable of attenuating the impact of a nominal propulsive
	landing with hazard avoidance and tolerant to off nominal performance of both hazard detection and
Robust Landing	avoidance systems and descent systems.
	Conduct high fidelity end-to-end simulations of Generation 2 EDL systems to validate mission
	concepts. Evaluate performance and risk. Support project life cycle needs ranging from off-line
EDL Mission Simulation	mission simulation to real time mission simulation.



Surface Power




WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Radioisotopic Power	Provide sustained presence and survivability for long duration missions on the surface of Mars through the use of radioisotopic power conversion technology. Conserve Plutonium through the use of high efficiency energy converters
Solar Power	Improve solar collection efficiency on the Mars surface by developing improved means of dust removal.
Power Storage	Improve the performance of batteries at low temperatures. Develop batteries with lower survival temperatures (need to discuss with Rao Surumpudi and update.



Mars Sample Return Technologies



WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Forward Planetary Protection	Protect Mars from contamination from Earth-sourced organisms and preventing the introduction of Earth-sourced organisms into the returned sample. Validate the effectiveness of these techniques using precision analysis and modeling techniques.
Mars Ascent Vehicle	Inject a canister containing the sample into Mars orbit, deep space or an Earth return trajectory to accomplish the most efficient and cost effective transfer of the sample to Earth. Validate the performance and reliability of the vehicle.
Sample Tracking Rendezvous & Capture	Track, rendezvous and capture a canister containing the Mars sample in Mars orbit, deep space or in Earth orbit. Valdiate the performance and reliability of the recovery method.
Sample Containment and Earth Return	Provide containment of the returned sample, breaking the chain of contact with the Mars surface to the extent needed to meet planetary protection requirements. Validate usign Probabilistic Risk Assessment methods using ground and flight test data.
Returned Sample Handling	Retrieve the sample after landing or from Earth orbit. Contain and protect the sample during hazard assessment. Develop techniques of hazard assessment and investigation of the science value of the returned sample.



Regional Mobility and Subsurface Access




WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Rovers	Ability to transport payload extended distance over Mars surface terrains, to provide a platform for insitu science and a capability for sample acquisition and possibly ascent vehicle deployment
Aerial Vehicles	Ability to deploy payloads on extended flights in the Mars atmosphere primarily for the purpose of making observations of the Mars surface from a close vantage point.
Subsurface Access	Access to a range of depths in the Martian surface using drilling systems or robotic moles. These devices will bring samples to the surface or make insitu analyses
Science Operations	Develop software tools to assist operations of
and Visualization	landed assets on the surface of Mars.





Base Technologies



Science Instruments and Systems



WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Mars Instrument	Development of Ground Demonstrated Miniature
Development	Instruments (TRL 3,4) into Space Qualifiable
Program	Hardware (TRL 5,6) Ready for Response to Mars
_	Flight AO.
In-Situ Life Detection	Obtain evidence for past and present life on the
	subsurface and beneath the surface of Mars using
	in situ measurements
	Devise new techniques for life detection that make minimal assumptions about the nature of life on Mars.



Communication/Radio Navigation Technologies




WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Deep Space	Increase data return capability on "trunk line" deep space
Communications	link between Mars and Earth
	Increase lander direct-to-Earth data rate capabilities from 1 kbps (MER) to 10 kbps
Proximity Link	Provide proximity link relay communications capabilities
Communications	to enable increased data return and increased
	connectivity with future Mars assets
Radio-Based	Develop radio-based precision approach navigation
Navigation	capable of sub-km entry state knowledge
Protocols and Coding	Define Mars Network communications protocol
	architecture capable of evolvable, interoperable
	connectivity



Transportation/Orbit Insertion



WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Aercapture	Use aerodynamic lift and drag to enter Mars orbit from an approach trajectory with propulsion only used for control functions and periapsis raising
Space Propulsion	Develop lightweight chemical and electrical propulsion systems with smaller system mass and higher specific impulse.



Information Systems



WBS ELEMENT	DESCRIPTION - GOALS AND APPROACH
Missions Data Systems	Establish a unified approach to flight, ground, and test systems for
	EDL and landed assets.